

ELEPHANT

Low Pressure Paint
Transfer Pumps



The ELEPHANT series is engineered for reliable transfer of paint materials, oils, and explosive liquids. Ideal for feeding multiple spray guns and supporting paint circulation systems, this pump range ensures high-volume delivery up to 120 liters per minute and beyond. It is designed for high delivery up to 15 liters/min.

FEATURES

- ◆ Pneumatically sensed high-performance air motor
- ◆ High Flow Delivery
- ◆ Stainless Steel Hydraulic Body
- ◆ Easy Maintenance
- ◆ Ice-Free Air Motor Technology
- ◆ Non-turbulent flow

APPLICATIONS

- ◆ Designed for transferring large volumes of fluids like paints, adhesives, solvents, petrol, and diesel with ease.
- ◆ Its rugged construction ensures reliable performance in demanding industrial environments.

ACCESSORIES



TECHNICAL SPECIFICATIONS

Type	2:1000	2:2000	3:2000	2:4000	2:6500
Pressure ratio	2.5:1	2:1	3:1	2:1	2:1
Discharge per cycle (cc)	1000	2000	2000	4000	6500
Air motor piston diameter (mm)	125	160	202	250	250
Stroke Length (mm)	120	120	120	120	120
Recommended spray volume @15 cycles/min (lpm)	20	40	40	40	130
Maximum inlet air pressure (bar)	6	6	6	6	6
Maximum output pressure @ 6 bar air inlet	15	12	18	12	12
Air consumption N-LPM @ 15 cycles / minute	413	676	1050	1650	2749
CFM @ 6 bar @ 15 cycles	14.6	23.9	37.3	58.3	97.1



VR Coatings Pvt.Ltd.

Registered Office:
J-138 MIDC,
Bhosari, Pune 411026
Maharashtra,INDIA

☎ +91 98 2291 29 14
✉ sales@vrcoatings.com
🌐 www.vrcoatings.com

